



- Polycarbonate non-corrosive fittings with integrated LED light source
- IP65 rating for outdoor use
- 30,000 hour life
- 4000K cool white colour
- 120° beam angle
- IK06 impact rating
- Available in 4ft and 5ft
- Available in standard, microwave sensor and emergency mode versions
- Emergency version has integrated 3 hour emergency battery

IP65 Rated

30,000 hour life

Available in 4ft and 5ft

Available in standard, sensor and emergency versions

Code	Product Name	Watts	Useful Lumens	Total Lumens	Beam Angle	Height	Diameter	Length	MOQ
6959	Manto Integrated LED IP65 4FT Standard	40W	3200lm	3800lm	120°	83mm	101mm	1200mm	1
6966	Manto Integrated LED IP65 4FT Sensor	40W	3200lm	3800lm	120°	83mm	101mm	1200mm	1
6973	Manto Integrated LED IP65 4FT Emergency	40W	3200lm	3800lm	120°	83mm	101mm	1200mm	1
6980	Manto Integrated LED IP65 5FT Standard	55W	4700lm	5200lm	120°	83mm	101mm	1200mm	1
6997	Manto Integrated LED IP65 5FT Sensor	55W	4700lm	5200lm	120°	83mm	101mm	1200mm	1
7000	Manto Integrated LED IP65 5FT Emergency	55W	4700lm	5200lm	120°	83mm	101mm	1200mm	1

Experts in lighting since 1878

Crompton Lamps Limited registered in England and Wales No. 05590551  
Registered office and correspondence address: Unit 2, Marrtree Business Park, Bowling Back Lane, Bradford BD4 8QE

Tel: +44 (0)1274 657 088 Fax: +44 (0)1274 657 087 Email: sales@cromptonlamps.com Web: www.cromptonlamps.com

All images and specifications are for illustration purposes only and are subject to change without notice. E. & O. E. © Crompton Lamps Limited 2017.



theLIA  
MEMBER